IN THE CLAIMS:

1. (Currently Amended) A communications system comprising:

a plurality of regional ground stations;

a plurality of satellites located in an elliptical subgeostationary sub-geosynchronous orbit with respect to the earth, said satellites operating in a service area in a synchronized manner to provide continuous coverage to said service area, said satellites generating a plurality of beams with variable beam widths to obtain a substantially uniform cell size covering said service area; and

a plurality of user terminals within the service area receiving communication signals from the satellite.

2. (Original) A system as recited in claim 1 wherein said ground station is coupled to one selected from the group consisting of an internet service provider, a broadcast television center and a corporate internet.

- 3. (Original) A communications system as recited in claim 1 wherein said uniform cells are substantially fixed within said service area.
- 4. (Original) A communications system as recited in claim 1 wherein said plurality of beams provide equal capacity density to said cell size.
- 5. (Original) A communications system as recited in claim wherein said minimum elevation angle is greater than 10 degrees in said service area.

543

Bly

6. (Original) A communications system as recited in claim
wherein within said service area is a primary market area

7. (Original) A communications system as recited in claim 1 wherein said first plurality of satellites comprise a phase array to form said plurality of beams.

8. (Original) A communications system as recited in claim wherein said satellites are disabled when coextensive with a geostationary orbit.

9. (Original) A communications system as recited in claim
1 wherein said first plurality comprises less than 9 satellites.

10. (Original) A communications system as recited in claim 1 wherein said first plurality comprises 4 satellites.

11 (Original) A communications system as recited in claim
1 wherein said first plurality comprises 5 satellites.

12. (Currently Amended) A communications system comprising:

a first plurality of satellites located in an elliptical subgeostationary sub-geosynchronous orbit with respect to the earth, said satellites operating in a service area in a synchronized manner to provide continuous coverage to said service area, said satellites generating a plurality of beams with variable beamwidth to obtain a substantially uniform cell size covering said service area, said first plurality of satellites providing a first system capacity; and

ड्युड इ

Bl

a second plurality of satellites deployed after said first

area.

plurality of satellites, said second plurality of satellites providing a second system capacity greater than the first system capacity.

13. (Original) A communications system as recited in claim
12 wherein said uniform cells are substantially fixed within said service

14. (Original) A communications system as recited in claim
12 wherein said plurality of beams provide equal capacity density to said
cell size.

15. (Original) A communications system as recited in claim 12 wherein said minimum elevation angle is greater than 10 degrees in said service area.

16. (Original) A communications system as recited in claim 12 wherein within said service area is a primary market area having an elevation greater than 30°.

17. (Original) A communications system as recited in claim 12 wherein said first plurality of satellites comprise a phase array to form said plurality of beams.

18. (Original) A communications system as recited in claim
12 wherein said satellites are disabled when coextensive with a
geostationary orbit.

2018

B/x

SUB

19. (Original) A communications system as recited in claim 12 wherein said first plurality comprises less than 9 satellites.

20. (Original) A communications system as recited in claim 12 wherein said first plurality comprises 4 satellites.

2). (Original) A communications system as recited in claim 12 wherein said first plurality comprises 5 satellites.

22. (Original) A method of providing a system of inclined eccentric sub-geosynchronous satellite orbits above the earth, the method comprising:

defining at least one geographic service area within which satellite coverage is to be provided, said service area having a minimum elevation angle thereabove;

defining at least two satellite orbits above the minimum service area having a first satellite and a second respectively therein;

operating said first satellite to generate a plurality of fixed cells relative to the earth by varying the beamwidth of the beams generated during operation in an active arc of an orbit;

handing over operation from the first satellite to the second satellite to maintain at least the minimum elevation angle; and

operating said second satellite to generate the plurality of fixed cells by varying the beamwidth of the beams generated during operation in the active arc of an orbit.

उपन

23. (Currently Amended) A method communications system as recited in claim 19 12 wherein said satellite orbits are orbit is an inclined eccentric sub-geosynchronous orbit.

Page 6

24. (Previously Amended) A method as recited in claim 22 wherein said step of defining at least two satellite orbits comprises defining at least four orbits.

25. (Currently Amended) A method of developing a customized satellite constellation comprising the steps of:

developing a first satellite constellation having a first set of satellites having regional coverage having a first service area, wherein said first constellation comprises a first plurality of satellites located in an elliptical sub-geostationary sub-geosynchronous orbit with respect to the earth, said satellites operating in a service area in a synchronized manner to provide continuous coverage to said service area, said satellites generating a plurality of beams with variable beam widths formed as a function of orbit position to obtain a substantially uniform cell size covering said service area; and

launching a second set of satellites to form a second satellite constellation having primary market coverage in cooperation with said first set of satellites to have a second service area greater than said first service area.

- 26. (Previously Amended) A method as recited in claim 25 comprising launching a third set of satellites to form a third satellite constellation having optimized landmass coverage in cooperation with said first set of satellites and said second set of satellites having a third service area greater than said second service area.
- 27. (Currently Amended) A method as recited in claim 27 26 wherein said first constellation, said second constellation and said third constellation comprise SGSO satellites.
- 28. (Original) A method as recited in claim 26 wherein said first set of satellites are non-interfering with GSO satellites.
- 29. (Original) A method as recited in claim 26 wherein said second set of satellites are non-interfering with GSO satellites.

SOB

B/

Serial No. 09/536,275 ...

30. (Original) A method as recited in claim 27 wherein said first plurality of satellites and said second set of satellites have active arcs sized to provide continuous coverage to said second service area.

31. (Original) A method as recited in claim 27 wherein said first plurality of satellites and said second set of satellites have active arcs sized to be non-interfering with GSO satellites.

32. (Previously Added)

communications

system

comprising

a plurality of regional ground stations;

a plurality of satellites located in a elliptical sub-geostationary sub-geosynchronous orbit with respect to the earth, said satellites operating in a service area in a synchronized manner to provide continuous coverage to said service area, said satellites generating a plurality of beams with variable beam widths that vary as a function of orbital position to obtain a substantially uniform cell size covering said service area; and

a plurality of user terminals within the service area receiving communication signals from the satellite.

- 33. (Currently Amended) A communication communications system as recited in claim 32 wherein said plurality of satellites operate using a frequency of a GSO satellite.
- 34. (Currently Amended) A communication communications system as recited in claim 33 wherein said plurality of satellites do not operate in a GSO satellite avoidance zone.